

Predator Power Pre-Stretch

START



WRAP/RESET



TOP WRAPS



BOTTOM WRAPS



TURNTABLE



FILM CARRIAGE



TURNTABLE SPEED



CARRIAGE SPEED



FILM FORCE



STOP



POWER



Reliable PLC and easy-to-use controls provide dependable and consistent operation

- **Start** begins operation of the machine at the settings of all other controls.
- **Wrap/Reset** allows the user to select the wrap mode to wrap up only or wrap up and down. Reset brings the carriage and turntable to the home position.
- **Top and bottom wraps** place additional wraps of film at the top or bottom of your load for extra stability.
- **Turntable auto/manual** allows automatic or manual operation of the turntable.
- **Film carriage manual up, auto and manual down** allows for automatic or manual raising and lowering of the film carriage.
- **Turntable speed** adjusts the speed of the turntable for you particular load.
- **Carriage speed** allows you to adjust carriage speed for film overlap. The carriage can be stopped for additional "banding" wraps to reinforce the load.
- **Film force** precisely and consistently controls the film wrapping force applied to the load.
- **Stop** halts all machine functions immediately. Pull stop out and press start button to complete the wrapping cycle.
- **Power safety disconnect** must be ON to operate your Predator®
- **Electrical cabinet** with two keyed locks for safety and security.

System Specifications*

Pre-Stretch Gears.....	200%
	(others available 150%–300%)
Turntable Speed.....	Adjustable to 12 RPM
Wrap Height.....	to 80 inches
Motors.....	Baldor 90 VDC
Drive Boards.....	KB Electronics
Load Weight Capacity.....	4,000 pounds
Electrical.....	115 Volts, 15 Amps
Wrap Modes.....	2
	(Spiral Up/Down & Spiral Up Only)
Machine Weight.....	1,260 Pounds
Available in low or high profile and with optional ramp.	
*Subject to change without notice.	

Contact:

PREDATOR
POWER PRE-STRETCH

Low Profile with Optional Ramp



High Profile

HIGHLIGHT
INDUSTRIES, INC.

2694 Prairie SW, Grand Rapids, Michigan 49509
800-531-2465 • 616-531-2464 • Fax: 616-531-0506